

製品概要

BAS21DW5: 250 V Switching Diode

技術情報は、データシートをご参照ください。

The high voltage switching diode is designed for high voltage, high speed switching applications. This dual diode device contains two electrically isolated high voltage switching diodes encapsulated in a SOT-23 surface mount package.

特長

- These Devices are Pb-free, Halogen Free/BFR Free and are RoHS Compliant
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AECQ101 Qualified and PPAP Capable

電氣的仕様

製品	Pricing (\$/Unit)	Compliance	Status	Configuration	V_R Min (V)	V_F Max (V)	I_R Max (μ A)	I_F Max (A)	t_r Max (ns)	C_D Max (pF)	Package Type
BAS21DW5T1G	0.026	Pb-free Halide free	Active	Dual	250	1	0.1	0.2	50	5	SC-88A / SC-70-5
SBAS21DW5T1G	0.0708	AEC Qualified PPAP Capable Pb-free Halide free	Active	Dual	250	1	0.1	0.2	50	5	SC-88A / SC-70-5
SBAS21DW5T3G	0.066	AEC Qualified PPAP Capable Pb-free Halide free	Active	Dual	250	1	0.1	0.2	50	5	SC-88A / SC-70-5

詳細は、弊社 www.onsemi.jp の営業または販売代理店にお問い合わせください。

8/13/2020 作成