

製品概要

BAV99L: 100 V Switching Diode, dual, series

技術情報は、データシートをご参照ください。

The switching diode is designed for high speed switching applications. This dual diode device contains two diodes in series encapsulated in a SOT-23 surface mount package.

特長

- Pb-Free Packages are Available
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AECQ101 Qualified and PPAP Capable

電気的仕様

製品	Compliance	Status	Configuration	V_R Min (V)	V_F Max (V)	I_R Max (μ A)	I_F Max (A)	t_{rr} Max (ns)	C_D Max (pF)	Package Type
BAV99LT1G	Pb-free	Active	Series	100	1	1	0.215	6	1.5	SOT-23-3
	Halide free									
BAV99LT3G	Pb-free	Active	Series	100	1	1	0.215	6	1.5	SOT-23-3
	Halide free									
SBAV99LT1G	AEC Qualified	Active	Series	100	1	1	0.215	6	1.5	SOT-23-3
	PPAP Capable									
	Pb-free									
	Halide free									
SBAV99LT3G	AEC Qualified	Active	Series	100	1	1	0.215	6	1.5	SOT-23-3
	PPAP Capable									
	Pb-free									
	Halide free									

詳細は、弊社 www.onsemi.jp の営業または販売代理店にお問い合わせください。

8/18/2019 作成