

製品概要

MMSD914: Switching Diode, High Speed, 100 V

技術情報は、データシートをご参照ください。

The switching diode is designed for high speed switching applications. This device is housed in a SOD-123 surface mount package which is ideal for automated insertion.

特長

- SOD-123 Surface Mount Package
- High Breakdown Voltage
- Fast Speed Switching Time
- Pb-Free Packages are Available
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AECQ101 Qualified and PPAP Capable

電氣的仕様

製品	Pricing (\$/Unit)	Compliance	Status	Configuration	V_R Min (V)	V_F Max (V)	I_R Max (μ A)	I_F Max (A)	t_r Max (ns)	C_D Max (pF)	Package Type
MMSD914T1G	0.0181	Pb-free Halide free	Active	Single	100	1	5	0.2	4	4	SOD-123
MMSD914T3G	0.0181	Pb-free Halide free	Active	Single	100	1	5	0.2	4	4	SOD-123
SMMSD914T1G	0.0504	AEC Qualified PPAP Capable Pb-free Halide free	Active	Single	100	1	5	0.2	4	4	SOD-123
SMMSD914T3G	0.0423	AEC Qualified PPAP Capable Pb-free Halide free	Active	Single	100	1	5	0.2	4	4	SOD-123

詳細は、弊社 www.onsemi.jp の営業または販売代理店にお問い合わせください。

12/12/2019 作成