

FODM217D

DC 4

FODM217 DC (GaAs) 4 (VISO) 3,750 VACRMS

- 80600% IF = 5 mAVCE = 5 VTA = 25°C - FODM217A - 80160% - FODM217B - 130260% - FODM217C - 200400% - FODM217D - 300600%
- - UL15773750 VACRMS 1 - DIN EN/IEC60747-5-5565 V
- 260°C
- Consumer Appliances
- DC-DC Merchant Power Supply
- Set Top Boxes

	Pricing (\$/Unit)	Compliance	Status	Channels	CTR (Min) (%)	CTR (Max) (%)	CTR tested @ IF (mA)	V _{CE(sat)} (Max) (V)	BV _{CE0} (Min) (V)	BV _{CO} (Min) (V)	BV _{CO} (Min) (V)	t _{on} (Max) (μs)	t _{off} (Max) (μs)	V _{ISO} (Min) (V)	T _{OPR} (Min) (°C)	T _{OPR} (Max) (°C)	Package Type
FODM217D	0.2091	Pb	Active	1	300	600	5	0.4	80	-	7	3	3	3750	-55	110	MFP-4
FODM217DR2	0.2191	Pb	Active	1	300	600	5	0.4	80	-	7	3	3	3750	-55	110	MFP-4
FODM217DR2V	0.2784	Pb	Active	1	300	600	5	0.4	80	-	7	3	3	3750	-55	110	MFP-4
FODM217DV	0.2809	Pb	Active	1	300	600	5	0.4	80	-	7	3	3	3750	-55	110	MFP-4