




## 5 PIN FLIP-CHIP, 0.9x1.4 CASE 499BG **ISSUE O**

**DATE 21 JUL 2009** 








# **BOTTOM VIEW**

### SOLDERING FOOTPRINT\*




\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

#### NOTES:

- DIMENSIONING AND TOLERANCING PER
- ASME Y14.5M, 1994.
  CONTROLLING DIMENSION: MILLIMETERS.
  COPLANARITY APPLIES TO SPHERICAL
  CROWNS OF SOLDER BALLS.

	MILLIMETERS		
DIM	MIN	MAX	
Α	0.44	0.50	
A1	0.15	0.19	
b	0.21	0.25	
D	0.90 BSC		
E	1.40 BSC		
е	0.50 BSC		

# **GENERIC MARKING DIAGRAM\***



XXXX = Specific Device Code = Assembly Location

= Year WW = Work Week

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot " ■", may or may not be present.

DOCUMENT NUMBER:	98AON42382E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	5 PIN FLIP-CHIP, 1.4X0.9, 0.5 PITCH		PAGE 1 OF 1

ON Semiconductor and (III) are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.